

ClinchPartner ClinchMaster MX4



Cordless clincher
call for best price

Sturdy metallic case with room for 4 additional clinching tongs, second battery and rapid charger

Key features

- Electro-hydraulic drive, memory-less 14.4 V Li-Ion technology
- Clinching force up to 60 kN
- Low weight, 2.4 kg, including battery
- Optimum cycle control with automatic return after finished clinching
- Manual override always possible
- BCI, Battery capacity indicator
- Fully charged in one hour
- Quick battery swap
- DDP, Deep discharge protection
- Clinching cycle time approx 2 s

Wide selection of clinching tongs


- T25 series with depth 25 mm
- T45 series with depth 45 mm
- Tong weight 1.15 kg only
- Tong change in a 5-second snap-out, snap-in process
- Tongs pivot +/- 180 degrees around the clincher axis
- Tongs adapted for the thickness at hand
 - * T1 for 2x0.5-2x0.8 mm
 - * T2 for 2x0.8-2x1.3 mm
 - * T3 for 2x1.3-2x1.6 mm
 - * T4 for 2x1.6-2x2.0 mm
- Tongs and tool kits patented or patents pending

Specifications approximate

Authorized Agent

MeFaCo International bvba,
Industrial Fasteners & Installation Tools
Industrieweg 2 (Zone Hoogveld); B-9200 Dendermonde (Belgium)
Tel. (+32) 0-52 203923; Fax. (+32) 0-52 219524
E-mail : info@mefaco-intl.com


MeFaCo
INDUSTRIAL FASTENERS AND TOOLS



Configuration sheet

Basic pack, composed of

- 1x Electrohydraulic D10 drive
- 1x Battery, 14.4 V, Li-Ion 1.65 Ah
- 1x Rapid charger for 230 V
- 1x Clinching tong with rectangular tool kit from the T25 or T45 series
- 1x Sturdy metallic case

Qty	Article number
	S 10 144 16 230 T 25 1
	S 10 144 16 230 T 25 2
	S 10 144 16 230 T 25 3
	S 10 144 16 230 T 25 4
	S 10 144 16 230 T 45 1
	S 10 144 16 230 T 45 2
	S 10 144 16 230 T 45 3
	S 10 144 16 230 T 45 4

Additional battery

- B10, 14.4 V, Li-Ion 3.2 Ah battery

Qty	Article number
	B 10 144 32

Additional clinching tongs for D10 drives, rectangular tool kit

Qty	Depth of bite	Thickness range	Article number
	25 mm	2x0.5-2x0.8 mm	T 25 1
	25 mm	2x0.8-2x1.3 mm	T 25 2
	25 mm	2x1.3-2x1.6 mm	T 25 3
	25 mm	2x1.6-2x2.0 mm	T 25 4
	45 mm	2x0.5-2x0.8 mm	T 45 1
	45 mm	2x0.8-2x1.3 mm	T 45 2
	45 mm	2x1.3-2x1.6 mm	T 45 3
	45 mm	2x1.6-2x2.0 mm	T 45 4

Mark your selections and quantities in the tables above

Authorized Agent